



Republika ng Pilipinas  
**PANGASIWAAN NG DAUNGAN NG PILIPINAS**  
(PHILIPPINE PORTS AUTHORITY)  
B F. Condominium Bldg  
Aduana, Intramuros, Manila

TELEPHONE NOS 47-92-04  
40-81-66  
48 24-93

April 4, 1986

PPA MEMORANDUM CIRCULAR  
NO. 19 - 86

19


T O : ALL PORT MANAGERS, SHIPPERS,  
AND ALL OTHERS CONCERNED

SUBJECT . Conversion Rate for Coke Breeze for Purposes  
of Port Charges Computation

In order to establish the proper basis for the computation of port charges due on coke breeze by setting up a standard conversion rate for various size ranges of coke breeze, the following guidelines are hereby issued:

1. For Maria Cristina Chemical Industries (MCCI), the stowage factor for coke breeze shall be 1.4844 cubic meter/ton (CM/T) or a conversion rate of 1.3106 revenue ton/metric ton (RT/MT).
2. For Electro Alloys Corporation (EAC), the stowage factor for coke breeze shall be 1.6911 CM/T or a conversion rate of 1.490 RT/MT.
3. For Ferro Chemical (Ferro Chem), the stowage factor for coke breeze shall be 1.323 CM/T or a conversion rate of 1.168 RT/MT.
4. All other corporations/firms importing coke breeze shall have the same stowage factor and/or conversion rate as that of Electro Alloys Corporation, unless otherwise satisfactorily proven.

This Circular takes effect immediately.

  
PRIMITIVO S. SOLIS, JR.  
General Manager

POED/POD  
JHS/CSV/cms