

REQUEST FOR QUOTATION



The Philippine Ports authority, Port Management Office of PMO-Panay/Guimaras (PPA, PMO-PNG) through its Bids and Awards Committee for the Procurement of Goods and Consultancy Services and for Engineering Projects will undertake an Alternative Method of Procurement through NP - Small Value in accordance with Section 34 of the New Government Procurement Act R.A. 12009.

Name of Project: **Supply and Delivery of Maintenance and Measuring Tools**

(See attached Specification of Tools)

Approved Budget : **PHP 311,703.00**
for the Contract

Deadline of Submission : **October 28, 2025 / 4:00 PM**

Requirements:

1. Please quote your best quotation in line with the attached specifications. (Annex A) Unless otherwise the Supplier has a registry file at PPA, PMO-PNG all quotations must be accompanied with the following documents:

- | | |
|--------------------------------------|--|
| a. Mayor's/Business Permit | c. BIR Certificate of Registration (Form 2303) |
| b. PhilGeps Registration Certificate | d. DTI or SEC Registration |

2. All quotations shall be inclusive of all cost/s and applicable taxes and shall be valid for a period of thirty (30) calendar days from the deadline of submission of quotations.

3. Quotations received in excess of the Approved Budget for the Contract (ABC) shall be automatically rejected.

4. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by the signatory or his/her duly authorized representative.

5. Quotations shall be submitted to the BAC-Secretariat, PPA, PMO-Panay/Guimaras, Administration Bldg., Bldg., Brgy. Loboc, La Paz, Iloilo City 5000 or email at supplyunit.ppa.pmpng@gmail.com

For further information, please refer to:

The BAC Secretariat, PPA, PMO-Panay/Guimaras
Telephone Nos.: (033) 3377791 to 93 loc. 102

Very truly yours,



ENGR. JERRY P. ABELLO

Chairperson, Bids and Awards Committee

Date of Posting: **October 24 - 27, 2025**

Reference

Quotation No.:	<u>25-068</u>
RIV No.:	<u>25-05-232</u>
PR No.:	<u>PNG -10228-25</u>

PRICE QUOTATION FORM

Company/Trader's Name : _____
Address : _____

ITEM NO.	ITEM & DESCRIPTION	(Pls. Specify Brand)	QTY.	UNIT	UNIT PRICE	TOTAL
	Maintenance and Measuring Tools		1	lot		
1	Laser Meter, 200m range (See attached specs)		2	unit		
2	Laser Meter, 50m range (See attached specs)		2	unit		
3	Wheel Meter, 5km (See attached specs)		2	unit		
4	Long Tape, 50m (See attached specs)		1	unit		
5	Measuring Tape, 5m		8	unit		
6	Pliers 7"		2	pcs		
7	Riveter					
	Sizes: 5/32"		1	pc		
	1/4"		1	pc		
8	Tin Cutter, 8"		2	pcs		
9	Screw driver SK 1/4" x 8", Flathead with insulated handle		2	pcs		
10	Philip Screw SK 1/4" x 8", with insulated handle		2	pcs		
11	Ball Hammer 1 lb.		2	pcs		
12	Welding gloves (leather)		3	pairs		
13	Tri-square (escuala) big		2	pcs		
14	Tri-square (escuala) small		2	pcs		
15	Heavy Duty Wheel Barrow, 150kg cap. (See attached specs)		3	unit		
16	Multi-Tester, Heavy Duty (Analog) (See attached specs)		8	unit		
17	Clamp Meter, Digital (See attached specs)		8	unit		
18	Heat Gun, 1800-W		1	pcs		
19	Electric Grinder (See attached specs)		1	pcs		
DELIVERY:	Shall be completed within <u>15</u> days from receipt of Purchase Order.			GRAND TOTAL :		

The above quoted prices are inclusive of all costs and applicable taxes.

VAT

NON VAT

Signature Over Printed Name

Mobile/Telephone No.

Date



PHILIPPINE
PORTS
AUTHORITY

PORTS PARADISE/QUEZON

ACKNOWLEDGMENT RECEIPT

This is to acknowledge receipt of the Request for Quotation, as described inside the box at the right, today .

by: _____

Printed Name & Signature

Tel. No.

(date)

To be returned not later than: _____

Quotation No.: 25-068

RIV No.: 25-05-232

P.R. No.: PNG -10228-25

Date: _____

TOOLS

1. LASER METER, 200m range
- Specifications:
- Laser Diode: 635nm, <1nW
- Measuring Range: 0.05 -250m
- Measuring Accuracy : ± 1mm
- Measuring Units : m, cm, ft, in
- Batteries: 4 x1.5V LR03 (AAA)
2. LASER METER, 50m range
- Specifications:
- Laser Diode: 515nm, <1nW
- Measuring Range: 0.05 -50m
- Measuring Accuracy : ± 1.5mm
- Measuring Units : m, cm, ft, in
- Batteries: 2 x1.5V LR6 (AA)
3. WHEEL METER, 5km (Walking Measure)
- Specifications:
- 12" aluminium wheel counts up to 5,000m with convenient push-button reset
- 2-section snap-lock handle with ergonomic handle (Telescopic)
- Built-in Kickstand
4. LONG TAPE, 50m
- Specifications:
- High impact, high visibility yellow ABS case
- 3/8 in (10mm) wide yellow blade w/ polymer coating for durability
5. HEAVY DUTY WHEEL BARROW, 150kg cap
- Specifications:
- Pneumatic wheel bearing with Two Tone Soft Grip Handle
- Load (kg):150
6. MULTI-TESTER, HEAVY DUTY (analog)

SPECIFICATIONS

	Measuring range	Accuracy
DCV (NULL)	0.1V/0.5/2.5/10/50/250/1000V(20kΩ/V)	±2.5% of full scale
ACV	±5/25V(40kΩ/V)	±5% of full scale
DCA	2.5/10/50/250/1000V(9kΩ/V)	±3% of full scale (10V : ±4%)
Resistance	50μ/2.5m/25m/0.25A	±2.5% of full scale
dB	2k/20k/200k/2M/20MΩ	±3% of arc
Continuity	-10dB~+62dB	±3% of full scale (10V : ±4%)
Battery check	LED : emitting light at 10Ω or less. Open voltage : 3V	
hFE	1.5V	
	1000 at x10 range(optional probe "HFE-6T" is necessary)	
Meter type	Taut-band meter	
Accuracy assurance temperature / humidity	23±2°C 75%RH max.	
Operating temperature / humidity	No condensation	
Storage temperature / humidity	5~31°C, 80%RH(Max).	
Bandwidth	31<~40°C, 80~50%RH(decreasing linearly)	
Battery	-10 to 50°C, 70% RH or less,	
Fuse	No Condensation	
Size / Mass	40Hz~20kHz(less than 50V : ±3%)	
Standard accessories included	R6P x 2, 6F22 x 1	
	Φ5.2 x 20mm(250V / 0.5A)	
	H150 x W100 x D37mm / approx.290g	
	Test lead(TL-61), Instruction manual	

7. CLAMP METER, digital

Specifications:

Function	Measuring range	Best accuracy	Resolution
ACA	400/1000A	±(1.7%+5)	0.1A
DCV	400m/4/40/400/600V	±(1.2%+3)	0.1mV
ACV	400m/4/40/400/600V	±(2.2%+5)	0.1mV
Resistance	400/4k/40k/400k/4M/40MΩ	±(1.2%+4)	0.1Ω
Continuity	Buzzer sounds at between 0Ω and 65Ω(±35Ω)Open voltage: approx. 0.4V		
Diode test	Open voltage: approx. 1.6V		
Sampling rate	3 times/sec.		
Bandwidth	ACA 50/60Hz (sine wave) ACV 50-500Hz (sine wave)		
Display	4000		
Clamp diameter/Conductor size	Φ42mm/20×54mm		
Battery	R03×2		
Battery life	Approx. 120 hrs. at DCV (Zinc-carbon battery)		
Size/Mass	H238×W95×D45mm/Approx.290g		
Safety standards	IEC61010 CAT.Ⅲ600V		

8. HEAT GUN

- Specifications:
- Rated Input Power : 1800W
 - Working Temp. : 50-600°C
 - Airflow : 250-600 l/min
 - Control, Airflow :3-stage

9. ELECTRIC GRINDER

- Specifications:
- Power Input : 670W
 - No-load speed : 12000 rpm
 - Spindle Thread : M10
 - Disc diameter : 100mm
 - Weight : 1.6 kg