



TERMS OF REFERENCE FOR

“Maintenance of TMO Building at Port of San Jose, Antique”

TABLE OF CONTENTS

- A. RATIONALE
- B. SCOPE OF UNDERTAKING/DESCRIPTION OF WORK
- C. BUDGETARY REQUIREMENTS
- D. TECHNICAL AND DOCUMENTARY REQUIREMENTS:
- E. OBLIGATIONS AND RESPONSIBILITIES
- F. DELIVERABLES
- G. SPECIFICATIONS
- H. CONTRACT DURATION
- I. INSPECTION AND TESTS

A. RATIONALE

1. This Terms of Reference (TOR) and Technical Specifications refer to the ***“Maintenance of TMO Building at Port of San Jose, Antique”*** with approved Program of Works (POW) charged to PMO Panay/Guimaras Repair and Maintenance Funds for C.Y 2026.
2. The procurement process shall be in accordance with the provisions of R.A. 12009 with its Revised Implementing Rules and Regulations.

B. SCOPE OF UNDERTAKING/DESCRIPTION OF WORK

- The scope of works to be rendered by the winning bidder shall be as follows:

1. General Expenses

- | | | |
|---|------|------|
| 1.01 Mobilization/Demobilization/ Clearing of project Site after project completion | I.s. | 1.00 |
| 1.02 General Expenses Includes pre-con survey and provision of temfacil | I.s. | 1.00 |
| 1.03 Provide Construction Safety and Health Program in the Execution of the project | I.s. | 1.00 |

2. MAINTENANCE OF COMFORT ROOMS & LAVATORY

- | | | |
|--|------|-------|
| 2.01 Removal of Existing Tiles, Fixtures and doors of Comfort Rooms including lavatory tiles | sq.m | 57.47 |
| 2.02 Supply, deliver and Install floor, wall and lavatory tiles | sq.m | 47.97 |
| 2.03 Supply, deliver and Install Doors & Cabinet accessories | sq.m | 9.50 |
| 2.04 Supply, deliver and install plumbing fixtures | lot | 1.00 |

3. MAINTENANCE OF WINDOWS

- | | | |
|--|-------|-------|
| 3.01 Removal of damaged windows and store to designated area | sq.m. | 41.47 |
| 3.02 Enclose portion of windows and existing ACU slot as detailed in the plan | sq.m | 11.66 |
| 3.03 Supply, deliver and install glass jalousie window, incldng. Installation of ACU framing | sq.m | 31.39 |

4. MAINTENANCE OF DAMAGED CEILING & DOOR

- | | | |
|---|------|-------|
| 4.01 Removal of existing damaged ceiling and damaged door | sq.m | 25.14 |
|---|------|-------|

4.02 Supply, deliver and Install ceiling as detailed in the plan	sq.m.	23.46
4.03 Supply, deliver and Install glass door as detailed in the Plan	sq.m	1.68
4.04 Painting Works for Newly Installed Ceiling	sq.m	23.46

5. WATERPROOFING OF ROOF DECK

5.01 Scrape/Cleaning of existing waterproofing, sealing and application of new waterproofing paint	sq.m	212.0
--	------	-------

6. REPAINTING OF EXISTING CYCLONE PERIMETER FENCE (4 spans)

6.01 Painting of Cyclone Fence (2 coats) including surface preparation	span	4.00
--	------	------

- The equipment needed for the project:
 - 1-unit Welding Machine
 - 1-unit Electric Grinder

C. BUDGETARY REQUIREMENTS

The Philippine Ports Authority, PMO-Panay/Guimaras through its CY 2026 corporate funds intend to apply the sum of **Nine Hundred Ninety-Three Thousand Four Hundred Ninety-Four and 28/100 (Php 993,494.28)** inclusive of VAT, being the Approved Budget for the Contract (ABC).

D. TECHNICAL AND DOCUMENTARY REQUIREMENTS:

The Service Contractor/provider shall submit the following documents to the Authority:

- PCAB License (Small A)
- DTI Certificate of Registration of Business Name or Sec Registration
- Current Mayor's Permit
- Phil-GEPS Registration
- VAT Certificate of Registration
- Current Tax Clearance issued by BIR
- Omnibus Sworn Statement
- List of Equipment, either owned, leased and/or has under Purchase Agreement to be used for the execution of the project, if applicable
- List of Key Personnel (Project Manager, Project Engineer, Construction Foreman, etc.)
- Bid Proposal / Quotation
- Bill of Quantities
- Detailed estimates including a summary sheet indicating the unit prices of construction materials, labor rates and equipment rentals used in coming up with the bid and Cash Flow/Bar Chart

E. OBLIGATIONS AND RESPONSIBILITIES

1. OF THE SERVICE CONTRACTOR/SERVICE PROVIDER:

- i. The Contractor shall carry out the Works properly and in accordance with this Contract. The Contractor shall provide all supervision, labor, Materials, Plant and Contractor's Equipment, which may be required. All Materials and Plant on Site shall be deemed to be the property of the Procuring Entity.
- ii. The Contractor shall commence execution of the Works on the Start Date and shall carry out the Works in accordance with the Program of Work submitted by the Contractor, as updated with the approval of the Procuring Entity's Representative, and complete them by the Intended Completion Date.

- iii. The Contractor shall be responsible for the safety of all activities on the Site.
 - iv. The Contractor shall carry out all instructions of the Procuring Entity's Representative that comply with the applicable laws where the Site is located.
 - v. The Contractor shall submit to the Authority the list of the company's key personnel to be assigned in the project.
 - vi. If the Procuring Entity's Representative asks the Contractor to remove a member of the Contractor's staff or work force, for justifiable cause, the Contractor shall ensure that the person leaves the Site within seven (7) days and has no further connection with the Work in this Contract.
 - vii. During Contract implementation, the Contractor and his subcontractors shall abide at all times by all labor laws, including child labor related enactments, and other relevant rules.
 - viii. The Contractor shall submit to the Procuring Entity for consent the name and particulars of the person authorized to receive instructions on behalf of the Contractor.
 - ix. The Contractor shall cooperate and share the Site with other contractors, public authorities, utilities, and the Procuring Entity between the dates given in the schedule of other contractors particularly when they shall require access to the Site. The Contractor shall also provide facilities and services for them during this period. The Procuring Entity may modify the schedule of other contractors, and shall notify the Contractor of any such modification thereto.
 - x. Should anything of historical or other interest or of significant value be unexpectedly discovered on the Site, it shall be the property of the Procuring Entity. The Contractor shall notify the Procuring Entity's Representative of such discoveries and carry out the Procuring Entity's Representative's instructions in dealing with them.
 - xi. Security and safety rules and regulation must at all-time be observed and implemented in adherence with the Authority security and safety requirements for the duration of the project.
 - xii. Clearing of project site after the project shall also be implemented.
 - xiii. Winning bidder/supplier shall shoulder all contingencies covering the foregoing projects without additional cost to PPA PMO Panay-Guimaras.
 - xiv. If in case of unforeseen time restrictions on the deliveries, execution of work or weather disturbances, the winning bidder/supplier shall immediately inform thru writing the Authority on the request for time extension/suspension thereto whichever applies.
 - xv. The Bidder, by the act of submitting its bid, shall be deemed to have inspected the site, determined the general characteristics of the contract works and the conditions for this Project and examine all instructions, forms, terms, and project requirements in the Bidding Documents.
 - xvi. If in case of defects/damaged, winning bidder/supplier shall replace all-inclusive items within **15 calendar days** from delivery otherwise the same shall be considered as INCOMPLETE DELIVERY and corresponding charges shall be deducted from the payable amount of the contract.
 - xvii. To guarantee the faithful performance by the winning Bidder of its obligations under the contract, it shall post a performance security within a maximum period of ten (10) calendar days from the receipt of the Notice of Award from the Procuring Entity and in no case later than the signing of the contract.
- 1.1. The Performance Security shall be denominated in Philippine Pesos and posted in favor of the Procuring Entity in an amount not less than the percentage of the total contract price in accordance with the following schedule:

Form of Performance Security	Amount of Performance Security (Not less than the Percentage of the Total Contract Price)
(a) Cash or cashier's/manager's check issued by a Universal or Commercial Bank. For biddings conducted by the LGUs, the Cashier's/Manager's Check may be issued by other banks certified by the BSP as authorized to issue such financial instrument.	Ten percent (10%)
(b) Bank draft/guarantee or irrevocable letter of credit issued by a Universal or Commercial Bank: Provided, however, that it shall be confirmed or authenticated by a Universal or Commercial Bank, if issued by a foreign bank. For biddings conducted by the LGUs, Bank Draft/Guarantee, or Irrevocable Letter of Credit may be issued by other banks certified by the BSP as authorized to issue such financial instrument.	
(c) Surety bond callable upon demand issued by a surety or insurance company duly certified by the Insurance Commission as authorized to issue such security.	Thirty percent (30%)

- 1.2. Failure of the successful Bidder to comply with the above-mentioned requirement shall constitute sufficient ground for the annulment of the award and forfeiture of the bid security, in which event the Procuring Entity shall have a fresh period to initiate and complete the post qualification of the second Lowest Calculated Bid. The procedure shall be repeated until LCRB is identified and selected for recommendation of contract award. However, if no Bidder passed post-qualification, the BAC shall declare the bidding a failure and conduct a re-bidding with re-advertisement, if necessary.

xviii. Any inquiry regarding the project must be directly refer to the Authority.

2. OF THE AUTHORITY

- Evaluate and Award the Contract to the winning bidder in accordance with the provision of RA 12009.
- Identify, supervise and monitor the activities during the fabrication works and related services.
- Pay to the service contractor the amount due to them as specified in the contract, actual accomplishment and presentation of Statement of Account supported with Acceptance Certificate, subject to existing government accounting rules and regulations.

F. DELIVERABLES

1. SET-UP AND DELIVERY

- All prices quoted should be express in peso and shall be inclusive of delivery and installation/set-up to site.
- Projects includes provision of Protective Personal Equipment (PPE's), First Aid Kit with Medicine, safety signage's and project signage during the duration of the project implementation.
- Project includes scaffoldings and provision of Temporary Field Office, location to be identified and assigned by the Authority.
- All material included in the projects must be delivered on site as prescribed.

2. WARRANTY

The project shall be covered by a warranty, duly evidenced by a Warranty Certificate intended for the project covering a period of one (1) year to commence a day after its final inspection and acceptance.

- For the procurement of Infrastructure Projects, the following warranties shall be made:
62.2.1 From the time project construction commenced up to final acceptance, the contractor shall assume full responsibility for the following: a) any damage or destruction of the works except those occasioned by force majeure; and b) safety, protection, security, and convenience of his personnel, third parties, and the public at large, as well as the works, equipment, installation and the like to be affected by his construction work.(a)

62.2.2 One (1) year from project completion up to final acceptance or the defects liability period.

62.2.2.1 The contractor shall undertake the repair works, at his own expense, of any damage to the infrastructure on account of the use of materials of inferior quality, within ninety (90) days from the time the HoPE has issued an order to undertake repair. In case of failure or refusal to comply with this mandate, the Procuring Entity shall undertake such repair works and shall be entitled to full reimbursement of expenses incurred therein upon demand.

62.2.2.2 The defects liability period shall be covered by the Performance Security of the contractor required in Section 39.1 of this IRR, which shall guarantee that the contractor performs his responsibilities stated in the immediately preceding Section. If the contractor fails to 115 As amended by GPPB Resolution No. 15-2020, dated 28 July 2020, published in the Official Gazette on 21 September 2020. The 2016 Revised Implementing Rules and Regulations – Annex “A” 92 comply with its obligations under Section 62.2.2.1 of the IRR, the Procuring Entity shall forfeit its performance security, subject its property(ies) to attachment or garnishment proceedings, and perpetually disqualify it from participating in any competitive bidding. All payables of the GoP in his favor shall be offset to recover the costs.

Form of Warranty Security	Amount of Warranty Security (Not less than the required percentage of the Total Contract Price)
a) Cash or Letter of Credit issued by a Universal or Commercial Bank: Provided, however, That the Letter of Credit shall be confirmed or authenticated by a Universal or Commercial Bank, if issued by a foreign bank. For biddings conducted by LGUs, the Letter of Credit may be issued by other banks certified by the BSP as authorized to issue such financial instrument.	Five percent (5%)

b) Bank guarantee confirmed by a Universal or Commercial Bank. For biddings conducted by LGUs, the bank draft/guarantee may be issued by other banks certified by the BSP as authorized to issue such financial instrument.	Ten percent (10%)
c) Surety bond callable upon demand issued by GSIS or a surety or insurance company duly certified by the Insurance Commission as authorized to issue such security.	Thirty percent (30%)

3. DOCUMENTATION

Photos of project before, during and after project implementation should be supported with visuals photos and as built plan duly signed by the contractor and the Authority and shall form part of the documents to be submitted upon request for payment of the project.

G. SPECIFICATIONS

The winning bidder must always refer and adhere to the approved plans of the project and specifications on the following items;

GENERAL CONDITIONS

All parts of the construction shall be finished with first class workmanship, to the fullest talent and meaning of all plans and these specifications, and to the entire satisfaction of the Engineer-in-charge.

The construction shall conform to all the requirements of the National Building Code.

CONCRETE WORKS

All concrete shall be mixed thoroughly until there is uniform distribution of the cement and aggregates, and should be deposited as nearly as practicable in its final position, care being taken to avoid segregation of the aggregates.

Water to be used for mixing shall be clean and free from injurious amount of oil, acids, alkalis, salts, and other organic materials.

PROPORTIONING OF CONCRETE

All concrete works shall be done in accordance with the standard specifications for plain and reinforced concrete as adopted by the Government. Cement to be used shall be APO Portland cement or any other equivalent brands more readily available in the locality. Alternative cements so selected must meet the requirements of Portland cements, and approved by the Architect or Engineer in charge of construction.

The following proportions of concrete shall be used for the various parts of the building:

Columns and footings - Class A (1 : 2 : 4)

Class A concrete shall be mixture of 1 part cement, 2 parts fine aggregate, and 4 parts coarse aggregate by volume, plus enough clean water to make the mixture into pliable paste.

The fine aggregate for concrete shall consist of natural sand, or inert materials with similar characteristics, having clean, hard and durable grains, free from organic matter or loam.

The coarse aggregate for concrete shall consist of crushed rock of durable and strong qualities, or clean and hard gravel. Size of the coarse aggregate to be used shall vary from 20mm to 25mm (3/4" to 1")

FORMS FOR CONCRETE WORKS

All forms of concrete shall be properly braced or connected together so as to maintain the correct position and shapes of the concrete members. Forms shall be constructed sufficiently tight to prevent bulging or seepage of water.

STEEL REINFORCING BARS

All steel reinforcing bars to be used in this construction shall consist of round deformed bars with lugs or projections on their sides to provide a greater bond between concrete and the steel. All steel reinforcing bars to be used shall be of Grade 40.

All steel reinforcing bars shall be accurately place and secured against displacement by tying them together at each bar intersection with Gauge no. 16 galvanized tie wire.

The steel reinforcing bars indicated in the footings, and columns shall conform to the number, size, and spacing as indicated in the drawings or schedule of steel reinforcements.

No metal reinforcement shall be installed in place unless it is free from rust, scale or other coatings, which will destroy or reduce the bond with concrete.

TILING WORKS

This item shall consist of the supply, delivery, and installation of floor and wall tiles as indicated in the approved plans, including all necessary adhesives, grout, trims, accessories, labor, tools, and equipment required to complete the work. All tile surfaces shall be laid on clean, sound, and properly prepared substrates. Tiles shall be of approved type, size, color, texture, and quality, free from cracks, chips, or other defects. Installation shall be carried out in accordance with the manufacturer's recommendations, ensuring proper alignment, uniform spacing, level surfaces, and true lines. Tile joints shall be filled with approved grout matching the tile color, and all excess grout and adhesive shall be removed upon completion. Finished tiled surfaces shall be smooth, even, and free from lippage, cracks, stains, or other imperfections. Any damaged or defective tiles shall be replaced at the Contractor's expense. The completed tiling work shall include all cutting, fitting, edge finishing, cleaning, and incidental works necessary to provide a complete and acceptable installation.

PLUMBING WORKS

This item shall consist of the supply, delivery, installation, testing, and commissioning of all plumbing systems, fixtures, fittings, pipes, valves, accessories, and appurtenances as shown on the approved plans and specified herein. All plumbing materials shall be new, of approved quality, and compliant with applicable codes and standards. Water supply lines shall be installed using approved pipes and fittings, properly supported and protected against damage. Drainage, waste, and vent piping shall be installed with the required slopes and alignment to ensure efficient flow and proper operation. Plumbing fixtures shall be securely mounted, connected, and tested for leaks and functionality. All joints shall be watertight, and all piping systems shall be subjected to pressure and leak testing prior to acceptance. Upon completion, the Contractor shall thoroughly clean the system and ensure that all plumbing installations are fully operational, free from defects, and approved by the Engineer.

INSTALLATION OF DECORATIVE ELEMENTS

This item shall consist of the fabrication, supply, delivery, and installation of decorative elements, architectural features, trims, moldings, cladding, accent panels, or other ornamental components as indicated in the approved plans and details. All decorative elements shall be fabricated from approved materials and installed in accordance with the manufacturer's recommendations and approved shop drawings. Surfaces shall be properly prepared before installation, and all components shall be securely anchored, aligned, and finished to achieve the intended architectural appearance. Joints, connections, and exposed edges shall be neatly executed and concealed where practicable. The Contractor shall ensure that all decorative elements are level, plumb, free from defects, and resistant to normal environmental conditions. The completed work shall include all fasteners, adhesives, supports, finishes, touch-ups, labor, tools, equipment, and incidental materials necessary to achieve a complete, durable, and aesthetically acceptable installation as approved by the Engineer.

PAINTING WORKS FOR CONCRETE, WOOD AND STEEL STEEL SURFACES

This item shall consist of the surface preparation, supply, and application of paint materials on all exposed concrete and steel surfaces as indicated in the plans or as directed by the Engineer. All painting materials shall be of approved quality and shall be delivered to the site in the manufacturer's original sealed containers bearing the brand name and specifications. Colors and finishes shall be subject to the approval of the Engineer prior to application.

Concrete surfaces shall be thoroughly cleaned and allowed to cure adequately before painting. All dirt, dust, grease, laitance, loose particles, and other contaminants shall be removed. Surface defects such as cracks, holes, and uneven areas shall be repaired using approved patching materials and allowed to dry completely. Concrete surfaces shall receive one (1) coat of masonry or concrete primer followed by at least two (2) coats of acrylic latex paint or approved equivalent, applied evenly to achieve a uniform color and finish.

Steel surfaces shall be cleaned of all rust, mill scale, oil, grease, dirt, welding residues, and other foreign matter by wire brushing, scraping, sanding, or other approved methods. Bare steel surfaces shall receive one (1) coat of anti-corrosive metal primer followed by two (2) coats of enamel paint or approved equivalent. Each coat shall be allowed to dry thoroughly before the application of the succeeding coat. Painting shall not be carried out during unfavorable weather conditions or when surfaces are damp or wet.

All wood surfaces shall be thoroughly cleaned, sanded smooth, and free from dust, grease, and other foreign matter before painting. Nail holes, cracks, and imperfections shall be filled with approved wood filler and sanded to produce a uniform surface. Woodwork shall receive one (1) coat of wood primer or sealer, followed by puttying as required, and two (2) coats of high-quality enamel, polyurethane, varnish, or other specified finish. Each coat shall be allowed to dry properly and lightly sanded before the application of succeeding coats. Finished surfaces shall exhibit a smooth, even appearance, free from brush marks, runs, sags, blisters, and discoloration. The color and finish shall be as approved by the Engineer or Owner.

All paint applications shall be performed in accordance with the manufacturer's recommendations and standard painting practices to ensure a smooth, uniform, and durable finish free from runs, sags, brush marks, blistering, or other defects. Any damaged or unsatisfactory painted surfaces shall be repaired or repainted at the Contractor's expense. The completed painting works shall include all labor, materials, equipment, tools, surface preparation, application, and incidental works necessary to achieve a complete and acceptable finish as approved by the Engineer.

APPLICATION OF WATER PROOFING MATERIALS

Surfaces to receive waterproofing shall be sound, clean, dry, and free from dust, oil, laitance, loose particles, and other contaminants. Cracks, honeycombs, and surface defects shall be repaired prior to application. Waterproofing materials shall consist of a high-quality elastomeric cementitious or liquid-applied membrane suitable for roofs, wet areas, balconies, gutters, and other exposed surfaces. The membrane shall be applied in the required number of coats to achieve the manufacturer's specified thickness, including reinforcement mesh where necessary. All joints, corners, penetrations, and critical areas shall receive additional treatment. Upon completion, waterproofed areas shall be subjected to a water ponding or flood test for a minimum of 24 hours to verify watertightness before covering or finishing works proceed.

GLASS WORKS

Glass works shall include the supply and installation of all glass panels, accessories, sealants, and hardware as indicated in the plans and specifications. Glass shall be of approved quality, free from defects, scratches, bubbles, distortions, or other imperfections. Thickness and type of glass shall conform to the approved drawings and intended application. Glass panels shall be accurately cut and installed plumb, level, and securely fixed in frames using approved glazing compounds, rubber gaskets, setting blocks, and sealants. All edges shall be properly finished and protected from damage during installation. Silicone sealants used shall be weather-resistant and compatible with the glass and framing materials. Upon completion, all glass surfaces shall be cleaned and left free from stains, adhesive residues, cracks, chips, and other defects, ensuring a neat and professional appearance.

H. CONTRACT DURATION

- Completion of the project is required within **Sixty (60) calendar days** upon receipt of Notice to Proceed

I. INSPECTION AND TESTS


- Items/Units shall be brought/deliver to site and shall undergo in testing and/or inspection by PPA Representative upon completion of the project whenever applicable.
- Once the project reaches an accomplishment of ninety-five (95%) of the total contract amount, the Procuring Entity may create an inspectorate team to make preliminary inspection and submit a punch-list to the Contractor in preparation for the final turnover of the project. Said punch-list will contain, among others, the remaining Works, Work deficiencies for necessary corrections, and the specific duration/time to fully complete the project considering the approved remaining contract time. This, however, shall not preclude the claim of the Procuring Entity for liquidated damages.

Prepared and Submitted by:




ENGR. MAYLENE G. ARANTE
Manager, Engineering Service Division

Recommending Approval:



ENGR. ROBERT M. JALBUENA
BAC Chairperson
PMO-Panay/Guimaras

Approved by:



ENGR. RODEL G. LAGMAY
Port Manager
PMO-Panay/Guimaras

BID FORM

Date : _____
Project Identification No. : _____

To: **ENGR. RODEL G. LAGMAY, Port Manager**
Address: PMO Panay/Guimaras, Brgy. Loboc, Lapaz, Iloilo City

Having examined the Philippine Bidding Documents (PBDs) including the Supplemental or Bid Bulletin Numbers *[insert numbers]*, the receipt of which is hereby duly acknowledged, we, the undersigned, declare that:

- a. We have no reservation to the PBDs, including the Supplemental or Bid Bulletins, for the Procurement Project: ***“Maintenance of TMO Building at Port of San Jose, Antique”***;
- b. We offer to execute the Works for this Contract in accordance with the PBDs;
- c. The total price of our Bid in words and figures, excluding any discounts offered below is: *[insert information]*;
- d. The discounts offered and the methodology for their application are: *[insert information]*;
- e. The total bid price includes the cost of all taxes, such as, but not limited to: *[specify the applicable taxes, e.g. (i) value added tax (VAT), (ii) income tax, (iii) local taxes, and (iv) other fiscal levies and duties]*, which are itemized herein and reflected in the detailed estimates,
- f. Our Bid shall be valid within the a period stated in the PBDs, and it shall remain binding upon us at any time before the expiration of that period;
- g. If our Bid is accepted, we commit to obtain a Performance Security in the amount of *[insert percentage amount]* percent of the Contract Price for the due performance of the Contract, or a Performance Securing Declaration in lieu of the the allowable forms of Performance Security, subject to the terms and conditions of issued GPPB guidelines¹ for this purpose;
- h. We are not participating, as Bidders, in more than one Bid in this bidding process, other than alternative offers in accordance with the Bidding Documents;
- i. We understand that this Bid, together with your written acceptance thereof included in your notification of award, shall constitute a binding contract between us, until a formal Contract is prepared and executed; and
- j. We understand that you are not bound to accept the Lowest Calculated Bid or any other Bid that you may receive.
- k. We likewise certify/confirm that the undersigned, is the duly authorized representative of the bidder, and granted full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for the *[Name of Project]* of the *[Name of the Procuring Entity]*.
- l. We acknowledge that failure to sign each and every page of this Bid Form, including the Bill of Quantities, shall be a ground for the rejection of our bid.

¹ currently based on GPPB Resolution No. 09-2020

Name: _____

Legal Capacity: _____

Signature: _____

Duly authorized to sign the Bid for and behalf of: _____

Date: _____

Bill of Quantities

Maintenance of TMO Building at Port of San Jose, Antique (MPF-PNG-09-2026)					
Item No.	Description	Unit	Quantity	Unit Price (Pesos)	Amount (Pesos)
I.	<u>General Expenses</u>				
1.01	<u>Mobilization/Demobilization/Clearing of project site after project completion</u> <u>Amount in Words</u> _____ and _____ centavos)	I.s	1.00		
1.02	<u>General Expenses Includes pre-con survey and provision of temfacil</u> <u>Amount in Words</u> _____ and _____ centavos)	I.s.	1.00		
1.03	<u>Provide Construction Safety and Health Program in the Execution of the project</u> <u>Amount in Words</u> _____ and _____ centavos)	I.s.	1.00		
II.	<u>Maintenance of Comfort Rooms & Lavatory</u>				
2.01	<u>Removal of Existing Tiles, Fixtures and doors of Comfort Rooms including lavatory tiles</u> <u>Amount in Words</u> _____ and _____ centavos)	Sq.m	57.47		
2.02	<u>Supply, deliver and Install floor, wall and lavatory tiles</u> <u>Amount in Words</u> _____ and _____ centavos)	Sq.m.	47.97		

2.03	<u>Supply, deliver and Install Doors & Cabinet</u> Amount in Words and centavos)	Sq.m.	9.50		
2.04	<u>Supply, deliver and install plumbing fixtures</u> Amount in Words and centavos)	lot	1.00		
III.	<u>MAINTENANCE OF WINDOWS</u>				
3.01	<u>Removal of Damaged Windows and store to designated area</u> Amount in Words and centavos)	Sq.m.	41.47		
3.02	<u>Enclose portion of windows and existing ACU slot as detailed in the plan</u> Amount in Words and centavos)	Sq.m.	11.66		
3.03	<u>Supply, deliver and install glass jalousie window, incldng. Installation of ACU framing</u> Amount in Words and centavos)	Sq.m.	31.39		
IV.	<u>REPLACEMENT OF DAMAGED CEILING & GLASS DOOR</u>				
4.01	<u>Removal of existing damaged ceiling and damaged door</u> Amount in Words and centavos)	Sq.m.	25.14		

4.02	<u>Supply, deliver and Install ceiling as detailed in the plan</u> Amount in Words and centavos)	Sq.m.	23.46		
4.03	<u>Supply, deliver and Install glass door as detailed in the plan</u> Amount in Words and centavos)	Sq.m.	1.68		
4.04	<u>Painting Works for Newly Installed Ceiling</u> Amount in Words and centavos)	Sq.m.	23.46		
V.	<u>WATERPROOFING OF ROOF DECK</u>				
5.01	<u>Scrape/Cleaning of existing waterproofing, sealing and application of new waterproofing paint</u> Amount in Words and centavos)	Sq.m.	212.00		
VI.	<u>REPAINTING OF EXISTING CYCLONE PERIMETER FENCE (4 SPANS)</u>				
6.01	<u>Painting of Cyclone Fence (2 coats) including surface preparation</u> Amount in Words and centavos)	Span	4.00		
Total					

Submitted by:

Name of the Representative of the Bidder _____ Date: _____

Position

Name of the Bidder